HP PageWide XL 8200 40-in Printer with High-capacity Stacker



High efficiency—the fastest large format printing¹ and cost-efficient production workflow



React immediately, and meet the tightest deadlines

- Respond immediately with the fastest largeformat printer¹—up to 30 D/A1 pgs/min²—endto-end productivity.
- Reliable technical prints with HP PageWide XL pigment inks—vivid color, crisp lines, fine detail beat LED.³
- Gain productivity—one device delivers mixed sizes/paper types in 50% of the time, no mono/color collating.⁴
- Start printing in 50% of the time⁵ with an ultra-fast processor, native PDF management, and HP SmartStream.

Boost efficiency, enhanced workflows and security

- The market's largest 15-inch touchscreen⁶ makes it easy to operate from the front and the back.
- Avoid errors and reduce reprints by automatically detecting hidden layers before printing with HP SmartStream
- Save preparation and finishing time by managing folder styles and adding job separators with HP SmartStream.
- Protect your network with the world's most secure printer⁷—control printer access, create security settings.

Full end-to-end solution, up to 50% less costs⁸

- Free up operator time with a high-capacity stacker, inline folders, auto-switch, and up to 6 rolls.
- Print monochrome and color technical documents at the same or lower cost than comparable LED printers.⁸
- Up to 10 times lower energy consumption than comparable LED printers.⁹
- Eco-Carton replaces plastic cartridge—80% reduction in plastic and 66% CO2e reduction¹⁰, free take back.¹¹



p. (800) 540-5048

e. info@bhfx.net / www.bhfx.net



Technical specifications

General	
Description	Large-format color printer
Technology	HP PageWide Technology
Applications	Line drawings; Maps; Orthophotos; Posters
Ink types	Pigment-based (C, M, Y, K)
Ink cartridges	4 (C, M, Y, K)
Cartridge size	1L
Printheads	8 (C, M, Y, K)
Average printhead life	32L
Printhead warranty	10 L or 12 months
Print resolution	1200 x 1200 dpi
Minimum line width	0.0008 in (HP-GL/2 addressable)
	±0.1% ¹
Line accuracy	20.170
Print speed	75 64
Maximum print speed	75 ft/min
A1/Arch D/ANSI D (long edge first)	30 pages/min, 1500 pages/hr
AO/Arch E/ANSI E (short edge first)	18 pages/min, 800 pages/hr
Warm-up time	No warm up
First page out	18 sec (from USB)
Media	
Media rolls	2 rolls default with auto-switching, expandable to 6 rolls
Roll size	11 to 40 in
Roll diameter	Up to 7 in
Roll core diameter	3 in
Grammage	19 to 53 lb
Media thickness	Up to 15.7 mil
Media types	Bond and recycled papers, poster papers, polypropylene, Tyvek papers, matte film
Media output (standard)	High-capacity stacker
Media output (optional)	Top stacker, online folder
Embedded controller	
Processor	Intel Core i5
Memory	16 GB DDR4
Hard drive	1×128 GB SSD, 1×500 GB HDD, both self-encrypted with AES-256
Print languages (standard)	HP-GL/2, TIFF, JPEG, Adobe PostScript 3, Adobe PDF 1.7
Remote management	HP Partner Link, HP Embedded Web Server, HP Web Jetadmin
Connectivity	
Interfaces	TCP/IP, BootP/DHCP, USB 2.0 host
Printing paths	HP SmartStream software (optional), HP PageWide XL print drivers (PDF, HP-GL/2, and PCL3)
User interface	
User interface	15.6-inch (396-mm) TFT (LED blacklight) 16:9-format HD capacitive touchscreen
Dimensions (w x d x h)	
Printer	Standard: 77 x 30.9 x 64.4 in; With high-capacity stacker: 77 x 80.3 x 64.4 in
Shipping	88.9 x 40.9 x 62.1 in
Weight	
Printer	1274 lb
Shipping	1625 lb



BHFX Imaging

p. (800) 540-5048

e. info@bhfx.net / www.bhfx.net















on AU/E pfritting theteriate in Less to increase the first ink.

BMG trademark license code FSC®-C115319, see http://www.fsc.org. HP trademark license code FSC®-C017543, see http://www.fsc.org. Not all FSC®-certified products are available in all regions. For information about HP large format printing materials, please visit http://www.HPLFMedia.com.

Can be recycled through commonly available recycling programs.

ENERGY STAR® 3.0 compliant, less energy; EPEAT® Gold certified/environmentally preferred product¹ Eco-Carton replaces plastic cartridge with 80% reduction in plastic, achieves 66% CO2e reduction² Zero landfill—local outer carton recycling, free take-back of inner ink bag and printheads³ Inks are UL ECOLOGO® Certified and verified for Nordic Swan Ecolabeled printing companies⁴

¹ ENERGY STAR® 3.0 compliant for less energy use. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT Gold as of April, 2021. EPEAT® registered where applicable. EPEAT registration varies by country. See http://www.epeat.net for registration

registred where applicable. EPEAT registration varies by Country, See http://www.epeat.net.for/registration status by country ased on moving from plastic ink cartridge to cardboard HP Eco-Carton ink cartridge, with annual manufacturing savings of 36 tons and transport savings of 1 ton. Equivalent to 147,755 km (91,811 miles) driven by an average passenger vehicle or 4,718,692 million smartphones charged.

3 The ink cartridge HP Eco-Carton outer carton is 100% recyclable through local cardboard/paper programs. Inner materials including the ink bag are 55% recyclable and can be returned free of charge to the HP Planet Partners program for reprocessing of plastic parts. Zero landfill. For take-back of ink bag/finitheads/prints, visit http://www.hp.com/recycle to see how to participate and for HP Planet Partners program availability, program may not be available in voir uir/stiction.







Environmental Operating temperature

Acoustics Sound pressure

Sound power Power

Consumption Requirements

Certification Safety

Electromagnetic

Environmental

Warranty

Product 4VW18B

2NH46AAE 2NH47AAE

5EK00A

8SB02A 8SB09A 8SF70A 8SW00A

8SW00AAE 8SW04A

8SW04AAF 8SW14A 8SW14AAE CZ320B

G6H50B

312Z2A 312Z4A

3WW73A 3WW99A

Original HP printing supplies

Original HP large format printing materials

HP Matte Polypropylene, 3-in Core

ECO highlights

Operating humidity

41 to 1049

Kazakhstan (EAC)

Ordering information

20 to 80% RH, depending on media type

≤60 dB(A) (operating), ≤36 dB(A) (idle), ≤20 dB(A) (sleep) ≤7.8 B(A) (operating), ≤5.5 B(A) (idle), ≤3.5 B(A) (sleep)

HP PageWide XL 8200 40-in Printer with High-capacity Stacker

HP SmartStream Preflight Manager
HP SmartStream Print Controller USB for HP PageWide XL 5/6/8000 Printer series

HP SmartSream Print Controller for HP PageWide XL 5/6/8000 Printer series
HP SmartTracker USB for HP PageWide XL 5/6/8000 Printer series
HP SmartTracker for HP PageWide XL 5/6/8000 Printer series

HP SmartStream Document Organizer Module HP SmartStream Pixel Analysis Module

HP SmartStream USB Preflight Manager

HP PageWide XL Drawer HP PageWide XL Folder Upgrade Kit for Long Plots HP F70 Folder

HP 878 1-liter Cyan PageWide XL Ink Cartridge HP 878 1-liter Magenta PageWide XL Ink Cartridge

HP 878 1-liter Yellow PageWide XL Ink Cartridge HP 874/876 PageWide XL Cleaning Container HP 841/874/876 PageWide XL Cleaning Container HP 841/874/876 PageWide XL Maintenance Cartridge HP 841/874 PageWide XL Printhead

HP 868 1-liter Black PageWide XL Ink Cartridge

HP Universal Bond Paper, 3-in Core (FSC® certified)² (recyclable)³
HP Production Matte Poster Paper, 3-in Core (FSC® certified)² (recyclable)³
HP Production Satin Poster Paper, 3-in Core (FSC® certified)² (recyclable)³
HP Universal Heavyweight Coated Paper, 3-in Core (FSC® certified)² (recyclable)³

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Please recycle printing hardware and eligible printing supplies. Find out how at our website: http://www.hp.com/ecosolutions

HP HD Pro 2 42-in Scanner

HP PageWide XL Top Stacker

HP SD Pro 44-in Scanner

0.37 kW (typical); 1.2 kW (max printing); 120 W (ready); <1 W (<16 W with embedded Digital Front End) (sleep)

IEC 60950-1+A1+A2 and IEC 62368-1 2nd ed. compliant; USA and Canada (CSA listed); EU (LVD and EN 60950-1 and 62368-1 compliant); Russia, Belarus, and

Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KC)

ENERGY STAR, EPEAT Registered, CE marking (including RoHS, WEEE, REACH). In compliance with WW RoHS materials restriction requirements in China, Korea, India, Vietnam, Turkey, Serbia, and Ukraine

Input voltage (auto ranging) 200-240 V (±10%), 50/60 Hz (±3 Hz), 8 A





